

Headquarters

**SPEKTRA Schwingungstechnik und
 Akustik GmbH Dresden**

Heidelberger Str. 12
 01189 Dresden
 Germany



Telephone: +49 351 400 24 0
Fax: +49 351 400 24 99
Email: sales@spektra-dresden.com
Web: www.spektra-dresden.com

US Office

SPEKTRA USA

32124 Paseo Adelanto, Suite 3
 San Juan Capistrano, CA 92675



Telephone: +1-949-234-9791
Fax: +1-760-683-3184
Email: sales@spektra-usa.com
Web: www.spektra-usa.com



CV-10

Rugged & Mobile Calibration System

1. Variable Power Supply

- ✓ 100 V ... 230 V
- ✓ Battery operation up to 10 h

2. Reliable Reference Transducer

- ✓ Reference transducer inside shaker table (standard)
- ✓ External back-to-back transducer (option)

3. Flexible Signal Conditioners

- ✓ PE, IEPE, 20 mA Current (standard)
- ✓ Amplifier for PR transducers (option)
- ✓ Extension port for future options

4. High-Performance Operation

- ✓ Manual mode with presets
- ✓ Automatic stepped sine
- ✓ Automatic sweep (option)
- ✓ High-resolution color display

5. Enhanced Connectivity

- ✓ USB data exchange
- ✓ Ethernet connection for PC software (option)
- ✓ Wi-Fi (option)

6. Powerful Vibration Exciter

- ✓ 5 Hz ... 10 kHz
- ✓ 200 m/s² (20 g) max
- ✓ 900 gram (2.0 lb) payload

